# **EU Safety Data Sheet**

#### In accordance with 2001/58/EG

## **BOTZ Stoneware-glaze 9880 Pazifik**

Prepared: 05.01.2006

# 1. Substance/Preparation and company description

1.1 Description of the substance or the preparation

## **BOTZ Stoneware-glaze 9880 Pazifik**

1.2 Use of the substance

Glassy overcoat of ceramic products

1.3 Company name

S K G Keramische Farben GmbH Hafenweg 26 a, 48155 Münster

Phone: +49 (0)251-65402 FAX: +49 (0)251-663012

Contact: Mechthild Surmann E-Mail: <u>botz-glasuren@t-online.de</u> Internet: <u>www.botz-glasuren.de</u>

1.4 Emergency contact number

Phone: +49 (0)251-65402

# 2. Composition/Constituent specifications

Mineral compound, milled glass, solvent-free binder based on acrylic

CAS-Nr. EINECS-Nr. Material description Content Symbols R-phrases S-phrases 68187-40-6 269-093-5 Pigment based on max. 5 % Xn R20/22 S20/21 Cobalt silicate

Xn (harmful to health)

# Possible hazards

No hazardous substance or preparation within the meaning of the Dangerous Chemicals Ordinance and/or EEC directives.

No hazards when used as intended. When misused (e.g., swallowing), no hazardous effects on human health have become known.

## 4. First-aid measures

After eye contact: rinse with water and consult a physician.

After swallowing: rinse mouth with water and consult a physician.

After contact with skin: wash off with water and soap.

# 5. Fire-fighting measures

Extinguishing agent: No restrictions.

# 6. Measures upon unintended release

Pick up and collect after spillage or leakage. Prevent skin and eye contact. Prevent emptying into drains.

# 7. Handling and storage

# 7.1 Handling

Do not eat, drink, or smoke while glazing. Wash hands directly after use. Thoroughly ventilate spaces during firing, if possible, discharge firing gases directly into the open air.

#### 7.2 Storage

Store closed container in a place inaccessible to children.

# 8. Exposition limits

## 8.1 Exposition limits

The product does not contain any relevant quantities of substances with workplacerelated limiting values to be monitored.

## 8.2 Limitation and monitoring of the exposition

# 8.2.1 Limitation and monitoring of the exposition at the workplace

Wear suitable gloves made of nitrile.

Avoid contact with eyes and skin.

# 8.2.2 Limitation and monitoring of the environmental exposition

The use of the product requires a smoothly functioning exhaustion of the kilns and sufficient ventilation of the workspaces.

# 9. Physical and chemical properties

#### 9.1 General information

Appearance: Liquid, pasty, often grainy mixture

coloured differently.

Odour: No perceptible odour.

9.2 Important information on health and environmental protection and on safety

ph-value: 8.00-10.00
Boiling point Not determined
Boiling range Not determined

Flash point:

Combustibility

n.a.

Explosion hazard:

Fire-supporting properties:

Steam pressure:

n.a.

Relative density: Not determined Solubility: water soluble

Distribution coefficient: n.a.

Viscosity: tixotropic.

Vapour density: n.a. Evaporation speed: n.a.

## 9.3 Other information

Store in a frost-protected place.

# 10. Stability and reactivity

#### 10.1 Conditions to be avoided:

Not known

# 10.2. Substances to be avoided:

Not known

# 10.3 Hazardous decomposition products

Not known

# 11. Toxicology specifications

When handled properly and in accordance with the intended use, the product will not cause in our experience and available information any effects harmful to health.

# 12. Ecological specifications

# 12.1 Ecotoxicity

12.2 Mobility

The watery dispersion predominantly consists of water-insoluble, anorganic components which to a great extent can be separated mechanically in cleaning equipment.

Water contaminant class 1 - low hazardous to waters (WGK) self classification

# 12.3 Persistence and decomposability Not applicable

# 12.4 Bio-accumulation potential Not applicable

# 12.5 Other hazardous effects Not applicable

## 13. Notes on disposal

If residues and collected wastes cannot be re-used, they can be set in a ceramic vessel by one-time firing at approx. 900°C.

Otherwise, dispose of in accordance with local waste removal regulations. For treatment of the process water, a small sewage plant is recommended.

Waste key product: 080203

Aqueous suspensions which container ceramic materials.

# 14. Information on transportation

Not a hazardous transport good.

## 15. Regulations

Does not require a hazardous warning label according to the EU guidelines/Dangerous Chemicals Ordinance.

## 16. Other information

R 20/22: Harmful by inhalation and if swallowed

S 20/21: When using do not eat or drink

This information is based on the current status of knowledge and experience.