CTM POTTERS SUPPLIES

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information:

Product Name : Bone Ash

Chemical Name : Tricalcium phosphate

Synonyms : None

Company : CTM Potters Supplies

Unit 10A, Millpark Industrial Estate

White Cross Road Woodbury Salterton

Nr. Exeter

EX5 1EL
Telephone : 01395-233-077
Fax : 01395-233-905

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients CAS Number EC Number % of composition

Bone Ash 68439-86-1 2704235 100

The product is cattle bones which have been degelatinised to remove fats and protein, then calcined as $>1000^{\circ}$ C in an oxidising atmosphere to produce tricalcium phosphate. $CA_{10}(PO_4)_6(OH)_2$

3. HAZARD IDENTIFICATION

Inhalation: Excessive exposure may cause symptoms of chronic lung disease.

Ingestion: The product is of low solubility in body fluids and it is likely to be of low toxicity.

Eyes: May cause physical irritation and inflammation.

Skin: The material is not a primary irritant, but as with any abrasive powder it may give rise to minor irritation.

The wet powder may cause some irritation due to high pH.

4. FIRST AID MEASURES

General Recommendations:

Inhalation: Remove patient to fresh air, loosen tight clothing and seek medical attention.

Ingestion: Do not induce vomiting. Seek medical advice.

Eves: Wash immediately with copious amounts of water.

Skin: Wash affected areas with water.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Those suitable for surrounding fire conditions.

Special exposure hazards: None

Protective personal equipment: None other than those suitable for the surrounding fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Leaks & Spills: Use suitable vacuum equipment where reasonably practicable. Otherwise, damp down and

scoop into a receptacle.

Personal protective equipment: Respiratory protective equipment.

7. HANDLING AND STORAGE

Handling: Do not eat, drink, or smoke in areas where the material is used.

Wash thoroughly after handling the material.

Storage: Store in dry area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Adequate ventilation should be provided so that Occupational Exposure Limits are not

exceeded. Local Exhaust Ventilation is normally recommended.

Personal protective equipment: Where LEV is not practicable and exposure is likely to be excessive, approved respiratory

protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves

and overalls are recommended for prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: powder
Colour: white
Odour: odourless

Flash point (°C): N/A

Flammability: N/A

Explosive properties: Non-explosive

Oxidising properties: None
Specific gravity: 3-5

pH value: 7 (insoluble in water)

Melting point (⁰C): Not available

10. STABILTY AND REACTIVITY

Chemical stability: The material is stable.

Conditions/materials to avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization products: None

11. TOXICOLOGICAL INFORMATION

Acute toxicology: LD50 Oral: >2000mg/kg

LD50 Dermal: Not known LD50 inhalation: Not known

Health effects: Prolonged or repeated exposure above Occupational Exposure Standards may

cause fibrosis of the lungs.

12. ECOLOGICAL INFORMATION

Ecotoxicity: No specific data available but the product is not expected to present a hazard.

Persistence: No specific data available but the product is not expected to present a hazard.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with current waste disposal regulations (for UK – Control of Pollution (Special Waste) Regulations 1980). Landfill is the most appropriate method.

14. TRANSPORT INFORMATION

UN/SI No. Not classified UN Class Not classified Packing Group Not classified Road UK Not classified ADR Not classified Sea IMO Not classified Air **ICAO** Not classified

15. REGULATORY INFORMATION

EC Supply Labelling: Non hazardous

R-Phrases: None

S-Phrases: Optional for dusty powders

S20/21 when using do not eat, drink or smoke.

in case of insufficient ventilation wear suitable respiratory equipment.

UK Occupational exposures limits*: Mg/m³ 8 hr TWA % in product.

Dusts -

Total inhalable 10 -Total respirable 5 --

In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.

16. OTHER INFORMATION

References:

COSHH ACOP HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994

CHIP 96 Chemicals (Hazard Information and Packaging for Supply) Regulations 1996

CHIP SDS ACOPS HSC Approved Code of Practice for Safety Data Sheets in accordance with regulation 6 of the CHIP

regulations.

HSE EH40 HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSH

regulations.

Further information:

Data sheet producing department: CTM Potters Supplies

Telephone: 01395-233-077

Disclaimer:

The information contained in this safety data sheet has been prepared using the best available information, however in view of technical developments, this may alter. The material must only be used for its stated purpose and the information contained within this data sheet is offered solely for use in the evaluation of this product in respect of safety, health and environmental hazards. Due to the many factors outside our control when using this product, we cannot accept liability for any injury, accident, loss or damage caused through its use.

^{*}Refer to HSE Guidance note EH40